



Product Catalog

Table of Contents

Industrial Fiber Media Converter	2
Unmanaged Industrial (PoE) Switch	3
Industrial Gigabit PoE Injector	5
PoE Extender	6
Industrial Gigabit PoE Splitter	8
Layer 2 Managed Industrial Ethernet Switch	9
Industrial Serial Fiber Converter	11
Commercial Grade Ethernet Switch	12
Commercial Grade Media Converter	18
Video Transimmsion	19

Industrial Fiber Media Converter



WXA-I01G-1SFP Series

Port

1 x 10/100/1000BASE-TX RJ45
1 x 1000BASE-FX SC

Power Supply

12-48V DC(4-Pin Terminal Block)

Features

1-Port IEEE 802.3af/at/bt PoE Optional
IEEE 802.3x Flow control
Auto-MDI/MDI-X,Auto-Negotiation
Full/Half-duplex
Built-in surge protection
IP40 Rating
LC/ST/FC Optional

Environmental

-40~+75 Operating Temp

Mounting

DIN-Rail/ Wall-mount



WXA-I02G-1SFP Series

Port

1 x 10/100/1000BASE-TX RJ45
1 x 1000BASE-FX SC

Power Supply

12-48V DC(4-Pin Terminal Block)

Features

2-port IEEE 802.3af/at/bt PoE Optional
IEEE 802.3x Flow control
Auto-MDI/MDI-X,Auto-Negotiation
Full/Half-duplex
Built-in surge protection
IP40 Rating
LC/ST/FC Optional

Environmental

-40~+75 Operating Temp

Mounting

DIN-Rail/ Wall-mount



WXA-I01G-10GSFP+ Series

Port

1 x 100/1G/2.5G/5G/10G BASE-TX RJ45
1 x 10GBASE-X SFP+

Power Supply

12-48V DC(4-Pin Terminal Block)

Features

1-port IEEE 802.3af/at/bt PoE Optional
IEEE 802.3x Flow control
Auto-MDI/MDI-X,Auto-Negotiation
100Mbps, 1Gbps half/full duplex
2.5/5/10Gbps full duplex mode
Built-in surge protection
DIP Switch

Environmental

-40~+75 Operating Temp

Mounting

DIN-Rail/ Wall-mount

PoE Function Optional(48-57V DC Input When PoE In Use)

Unmanaged Industrial (PoE) Switch



WXA-I04G-1SFP Series (PoE Optional)

Port

4 x 10/100/1000BASE-TX RJ45
1 x 100/1000BASE-FX SFP

Power Supply

12-48V DC(4-Pin Terminal Block)

Features

4-port IEEE 802.3af/at PoE Optional
IEEE 802.3x Flow control
8K MAC Address
Auto-MDI/MDI-X,Auto-Negotiation
Full/Half-duplex
Built-in surge protection
IP40 Rating

Environmental

-40~+75 Operating Temp
5%~95%(No condensation) Humidity

Mounting

DIN-Rail / Wall-mount



WXA-I05G Series (PoE Optional)

Port

4 x 10/100/1000BASE-TX RJ45
1 X 10/100/1000BASE-TX Uplink

Power Supply

12-48V DC(4-Pin Terminal Block)

Features

4-port IEEE 802.3af/at PoE Optional
IEEE 802.3x Flow control
8K MAC Address
Auto-MDI/MDI-X,Auto-Negotiation
Full/Half-duplex

Built-in surge protection
IP40 Rating

Environmental

-40~+75 Operating Temp
5%~95%(No condensation) Humidity

Mounting

DIN-Rail / Wall-mount

Unmanaged Industrial (PoE) Switch



WXA-I08G Series (PoE Optional)

Port

8 x 10/100/1000BASE-TX RJ45

Power Supply

9-56V DC(6-Pin Terminal Block)

Features

8-port IEEE 802.3af/at/bt PoE Optional

20Gbps Bandwidth

1500 Bytes Frame

4K MAC Address

2M Buffer Size

IP40 Rating

Environmental

-40~+75 Operating Temp

Mounting

DIN-Rail / Wall-mount



WXA-I024G Series (PoE Optional)

Port

24 x 10/100/1000BASE-TX RJ45

Power Supply

9-56V DC(6-Pin Terminal Block)

Features

24-port IEEE 802.3af/at PoE Optional

52Gbps Bandwidth

10K Bytes Giant Frame

8K MAC Address

4M Buffer Size

IP40 Rating

Environmental

-40~+75 Operating Temp

Mounting

DIN-Rail / Wall-mount

Industrial Gigabit PoE Injector



WXA-INJ Series

Port

1 x Gigabit RJ45 Data In

1 x Gigabit RJ45 PoE(Data+Power) Out

Power Supply

12-48V DC(2-Pin Terminal Block)

Features

IEEE 802.3af/at/bt

Plug and Play

Built-in surge protection

IP40 Rating

Environmental

-40~+75°C Operating Temp

5%~95%(No condensation) Humidity

Mounting

DIN-Rail / Wall-mount

Customizable Passive PoE
(12/24/36V)

12-48V DC Input with Power Booster Function



Gigabit Port (2.5/5/10G Optional)



Full/Half-duplex



6KV Lightning Protection



Compact Size



Aluminum Housing



-40~+75°C
Operating Temp

Industrial Gigabit PoE Extender



WXA-IPE1T4 Series

Port

1 x Gigabit RJ45 PoE/PD
4x Gigabit RJ45 PoE/PSE

Input Voltage

50-57V DC

Features

IEEE 802.3af/at/bt
Plug and Play
Built-in surge protection

IP40 Rating

Environmental

-40~+75 Operating Temp
5%~95%(No condensation) Humidity

Mounting

DIN-Rail / Wall-mount



WXA-WP-IPE1T1

Port

1 x Gigabit RJ45 PoE/PD
1x Gigabit RJ45 PoE/PSE

Input Voltage

50-57V DC

Features

IEEE 802.3af/at/bt
Plug and Play
Built-in surge protection
IP67 waterproof & dustproof design

Environmental

-40~+75 Operating Temp
5%~95%(No condensation) Humidity

Mounting

Wall-mount



WXA-WP-IPE1T2

Port

1 x Gigabit RJ45 PoE/PD
2x Gigabit RJ45 PoE/PSE

Input Voltage

50-57V DC

Features

IEEE 802.3af/at/bt
Plug and Play
Built-in surge protection
IP67 waterproof & dustproof design

Environmental

-40~+75 Operating Temp
5%~95%(No condensation) Humidity

Mounting

Wall-mount

PoE Repeater



WXA-JB0104-AT Series

Port

1 x 10/100M RJ45 PoE/PD
4x 10/100M RJ45 PoE/PSE

Input Voltage

44-57V DC

Features

IEEE 802.3af/at
Plug and Play
Auto MDI/MDIX
2 VLAN IEEE STD 802.1Q

Environmental

-10~+50 Operating Temp



WXA-AT13F-A

Port

1 x 10/100M RJ45 PoE/PD
3x 10/100M RJ45 PoE/PSE

Input Voltage

44-57V DC

Features

IEEE 802.3af/at
One-Click VLAN
Waterproof Optional
Gigabit Speed Optional
Total PoE input power $\leq 30W$
Maximum power per port $\leq 24W$

Environmental

-10~+50 Operating Temp

Mounting

Din-rail



WXA-AT14F-A

Port

1 x 10/100M RJ45 PoE/PD
4x 10/100M RJ45 PoE/PSE

Input Voltage

44-57V DC

Features

IEEE 802.3af/at
One-Click VLAN
Waterproof Optional
Gigabit Speed Optional
Total PoE input power $\leq 90W$
Port 2 output power $\leq 60W$
Port 3 to 5 output power $\leq 30W$ each

Environmental

-10~+50 Operating Temp

Mounting

Din-rail

Industrial Gigabit PoE Splitter



WXA-SPLT30 Series

Port

1 x Gigabit RJ45 PoE(Data+Power) In
1x Gigabit RJ45 Data Out

Output Voltage

5/9/12/19V DC Output Optional(2-Pin Terminal Block)

Features

IEEE 802.3af/at
Plug and Play
Built-in surge protection
IP40 Rating

Environmental

-40~+75 Operating Temp
5%-95%(No condensation) Humidity

Mounting

DIN-Rail / Wall-mount



WXA-SPLT90 Series

Port

1 x Gigabit RJ45 PoE(Data+Power) In
1 x Gigabit RJ45 Data Out

Output Voltage

12/19/24/36V DC Output Optional(2-Pin Terminal Block)

Features

IEEE 802.3af/at/bt
Plug and Play
Built-in surge protection
IP40 Rating

Environmental

-40~+75 Operating Temp
5%-95%(No condensation) Humidity

Mounting

DIN-Rail / Wall-mount

Layer 2 Managed Industrial Ethernet Switch



WXA-L2I016GM Series

Port

16 x 10/100/1000BASE-TX RJ45

Power Supply

9-56V DC(6-Pin Terminal Block)

Features

Port 1-16 IEEE 802.3af/at PoE Optional

56Gbps Bandwidth

10K Jumbo Frame

8K MAC Address

4M Buffer Size

IP40 Rating

Environmental

-40~+75 Operating Temp

Mounting

DIN-Rail / Wall-mount



WXA-L2I016GM-4SFP Series

Port

16 x 10/100/1000BASE-TX RJ45
4 x 100/1000BASE-FX SFP

Power Supply

9-56V DC(6-Pin Terminal Block)

Features

Port 1-16 IEEE 802.3af/at PoE Optional

56Gbps Bandwidth

10K Jumbo Frame

8K MAC Address

4M Buffer Size

IP40 Rating

Environmental

-40~+75 Operating Temp

Mounting

DIN-Rail / Wall-mount



WXA-L2I016GM-8SFP Series

Port

16 x 10/100/1000BASE-TX RJ45
8 x 100/1000BASE-FX SFP

Power Supply

9-56V DC(6-Pin Terminal Block)

Features

Port 1-16 IEEE 802.3af/at PoE Optional

56Gbps Bandwidth

10K Jumbo Frame

8K MAC Address

4M Buffer Size

IP40 Rating

Environmental

-40~+75 Operating Temp

Mounting

DIN-Rail / Wall-mount

Layer 2 Managed Industrial Ethernet Switch



WXA-L2I08GM-2SFP Series

Port

8 x 10/100/1000BASE-TX RJ45
2 x 100/1000BASE-FX SFP

Power Supply

9-56V DC(6-Pin Terminal Block)

Features

36Gbps Bandwidth
10K Jumbo Frame
8K MAC Address
4M Buffer Size
IP40 Rating

Environmental

-40~+75 Operating Temp

Mounting

DIN-Rail / Wall-mount



WXA-L2I08GM Series

Port

8 x 10/100/1000BASE-TX RJ45

Power Supply

9-56V DC(6-Pin Terminal Block)

Features

36Gbps Bandwidth
10K Jumbo Frame
8K MAC Address
4M Buffer Size
IP40 Rating

Environmental

-40~+75 Operating Temp

Mounting

DIN-Rail / Wall-mount



WXA-L2I024GM-4SFP Series

Port

24 x 10/100/1000BASE-TX RJ45
4 x 100/1000BASE-FX SFP

Power Supply

9-56V DC(6-Pin Terminal Block)

Features

Port 1-24 IEEE 802.3af/at PoE Optional
56Gbps Bandwidth
10K Jumbo Frame
8K MAC Address
4M Buffer Size
IP40 Rating

Environmental

-40~+75 Operating Temp

Mounting

DIN-Rail / Wall-mount

Industrial Serial Fiber Converter



WXA-RS Series

Interface

- 1× SC/ST/FC/LC
- 1× RS232
- 1x RS485
- 2× RS485H

Power Supply

12-48V DC(2-Pin Terminal Block)

Features

- Bi-directional RS-232/485/422
- DMX512 for stage lighting control
- Built-in surge & ESD protection
- Diagnostic LED indicators

Environmental

-40~+75 Operating Temp

Mounting

DIN-Rail / Wall-mount



WXA-RS100-SFP

Interface

- 1 x 10/100BASE-T RJ45
- 1 x 100Base-FX
- 1 x RS232/RS485/RS422

Power Supply

12-48V DC(4-Pin Terminal Block)

Features

- Full/half-duplex, auto-negotiation
- Built-in 15KV ESD protection
- 1500W/sec surge protection
- Diagnostic LED indicators

Environmental

-40~+75 Operating Temp

Mounting

DIN-Rail / Wall-mount

Layer 2 Rack Mount Managed Industrial Ethernet Switch



WXA-L2RI016GM-8SFP-4C

Port

16 x 10/100/1000BASE-TX RJ45
8 x 100/1000BASE-FX SFP
4 x Gigabit SFP/RJ45 Combo

Power Supply

9-56V DC(5-Pin Terminal Block)

Features

Port 9-24 IEEE 802.3af/at PoE Optional
56Gbps Bandwidth
10K Jumbo Frame
8K MAC Address
4M Buffer Size
IP40 Rating

Environmental

-40~+75 Operating Temp

Mounting

Rack-mount



WXA-L2RI08GM-16SFP-4C

Port

8 x 10/100/1000BASE-TX RJ45
16 x 100/1000BASE-FX SFP
4 x Gigabit SFP/RJ45 Combo

Power Supply

9-56V DC(5-Pin Terminal Block)

Features

Port 17-24 IEEE 802.3af/at PoE Optional
56Gbps Bandwidth
10K Jumbo Frame
8K MAC Address
4M Buffer Size
IP40 Rating

Environmental

-40~+75 Operating Temp

Mounting

Rack-mount



WXA-L2RI024GM-2SFP

Port

24x 10/100/1000BASE-TX RJ45
2 x 100/1000BASE-FX SFP

Power Supply

9-56V DC(5-Pin Terminal Block)

100-240V AC Optional

Features

Port 1-24 IEEE 802.3af/at PoE Optional
10K Jumbo Frame
8K MAC Address
4M Buffer Size
IP40 Rating

Environmental

-40~+75 Operating Temp

Mounting

Rack-mount

Rack Mount Commercial Grade Ethernet Switch



WXA-C024G-2SFP Series

Port

24 x 10/100/1000BASE-TX RJ45
2 x 1000BASE-FX SFP

Power Supply

100-240V AC

Features

24-Port IEEE 802.3af/at PoE Optional
52Gbps Bandwidth
10K Jumbo Frame
8K MAC Address
4M Buffer Size
IP30 Rating

Environmental

0~50 Operating Temp

Mounting

Rack-mount



WXA-C024GM-2SFP Series

Port

24 x 10/100/1000BASE-TX RJ45
2 x 100/1000BASE-FX SFP

Power Supply

100-240V AC

Features

24-Port IEEE 802.3af/at/bt PoE Optional
52Gbps Bandwidth
10K Jumbo Frame
8K MAC Address
4M Buffer Size
IP30 Rating

Environmental

0~50 Operating Temp

Mounting

Rack-mount

Full Gigabit Light Managed PoE Switch with Web/Cloud Management APP



WXA-I04GM-C20P

Port

4 x 10/100/1000T 802.3at PoE
2 x 10/100/1000M Uplink

Power Supply

110-240V AC



WXA-I04GM-C11P

Port

4 x 10/100/1000T 802.3at PoE
1 x 10/100/1000M Uplink
1 x 1000X SFP

Power Supply

110-240V AC



WXA-I08GM-CP

Port

8 x 10/100/1000T 802.3at PoE

Power Supply

110-240V AC



WXA-I08GM-C02P

Port

8 x 10/100/1000T 802.3at PoE

Power Supply

110-240V AC



WXA-I016GM-C22P

Port

16 x 10/100/1000T 802.3at PoE
2 x 10/100/1000M Uplink
2 x 1000X SFP

Power Supply

110-240V AC

Mounting

Rack-mount



WXA-I024GM-C21P

Port

24 x 10/100/1000T 802.3at PoE
2 x 10/100/1000M Uplink
1 x 1000X SFP

Power Supply

110-240V AC

Mounting

Rack-mount



WXA-I024GM-C22P

Port

24 x 10/100/1000T 802.3at PoE
2 x 10/100/1000M Uplink
2 x 1000X SFP

Power Supply

110-240V AC

Mounting

Rack-mount

Features

- ▶ Port power control
- ▶ Multiple VLANs
- ▶ Link aggregation
- ▶ Storm suppression
- ▶ 4kV surge protection
- ▶ Operating temp -10-55°C

Full Gigabit Light Managed Ethernet Switch with Web/Cloud Management APP



WXA-I05GM-C

Port

5 x 10/100/1000T

Power Supply

12V DC



WXA-I05GM-C01

Port

4 x 10/100/1000T
1X1000X SFP

Power Supply

12V DC



WXA-I08GM-C

Port

8 x 10/100/1000T

Power Supply

12V DC



WXA-I016GM-C02

Port

16 x 10/100/1000T
2 x 1000X SFP

Power Supply

110-240V AC

Mounting

Rack-mount



WXA-I024GM-C01

Port

24 x 10/100/1000T
1 x 1000X SFP

Power Supply

110-240V AC

Mounting

Rack-mount

Features

- ▶ Port power control
- ▶ Multiple VLANs
- ▶ Link aggregation
- ▶ Storm suppression
- ▶ 4kV surge protection
- ▶ Operating temp -10-55°C

Full Gigabit PoE Switch



WXA-I04G-C01P

Port

4 x 10/100/1000T 802.3at PoE
1 x 1000X SFP

Features

AI Watchdog
One-Click VLAN
6KV Lightning Protection

Power Supply

110-240V AC



WXA-I04G-C11P

Port

4 x 10/100/1000T 802.3at PoE
2 x 10/100/1000M Uplink
1 x 1000X SFP

Features

AI Watchdog
One-Click VLAN
6KV Lightning Protection

Power Supply

110-240V AC



WXA-I08G-C20P

Port

8 x 10/100/1000T 802.3at PoE
2 x 10/100/1000M Uplink

Features

AI Watchdog
One-Click VLAN
6KV Lightning Protection

Power Supply

110-240V AC



WXA-I08G-C22P

Port

8 x 10/100/1000T 802.3at PoE
2 x 10/100/1000M Uplink
1 x 1000X SFP

Features

AI Watchdog
One-Click VLAN
6KV Lightning Protection
QoS Port Priority

Power Supply

110-240V AC



WXA-I08G-C21P

Port

8 x 10/100/1000T 802.3at PoE
2 x 10/100/1000M Uplink
1 x 1000X SFP

Features

AI Watchdog
One-Click VLAN
6KV Lightning Protection
QoS Port Priority

Power Supply

110-240V AC



WXA-I016G-C20P

Port

16 x 10/100/1000T 802.3at PoE
2 x 10/100/1000M Uplink

Features

One-Click VLAN
6KV Lightning Protection
QoS Port Priority

Power Supply

110-240V AC

Mounting

Rack-mount



WXA-I048G-C20P

Port

24 x 10/100/1000T 802.3at PoE
2 x 10/100/1000M Uplink

Features

6KV Lightning Protection

Power Supply

110-240V AC

Mounting

Rack-mount

Waterproof Full Gigabit PoE Switch



WXA-I04G-WP10P

Port

4 x 10/100/1000T 802.3at PoE
1 x 10/100/1000M Uplink

Features

AI Watchdog
One-Click VLAN
2KV Lightning Protection
250m long-distance transmission
Total power $\leq 75W$

Environmental

-10~55 Operating Temp

Power Supply

110-240V AC

Mounting

Wall-mount



WXA-I08G-WPAT

Port

8 x 10/100/1000T 802.3at PoE
1 x 1000X SFP

Features

AI Watchdog
One-Click VLAN
2KV Lightning Protection
250m long-distance transmission
Total power $\leq 120W$

Environmental

-10~55 Operating Temp

Power Supply

110-240V AC

Mounting

Wall-mount



WXA-I08G-WP20P

Port

8 x 10/100/1000T 802.3at PoE
2 x 10/100/1000M Uplink

Features

2KV Lightning Protection
Total power $\leq 120W$

Environmental

-10~55 Operating Temp

Power Supply

110-240V AC

Mounting

Wall-mount

Commercial Grade Media Converter



WXA-C01G-1SFP

Port

1 x 10/100/1000T RJ45
1 x 1000X SFP

Features

9K jumbo frames
Complies with full IEEE standards
compatible with 3 fiber modes
SFP port dual-mode adaptive

Power Supply

5-18V DC

Environmental

0~45 Operating Temp



WXA-C01G-1SC Series

Port

1 x 10/100/1000T RJ45
1 x 1000X SC

Features

Max 120km transmission
Auto MDI/MDI-X and full/half duplex
MM/SM dual-fiber/SM single fiber (WDM)
SC/FC/LC/SFP optional

Power Supply

5V DC

Environmental

-10~55 Operating Temp

HDMI over Fiber Converter



WXA-4K-KVM

Interface(Female)

HDMI Type-A Tx In/Rx Out

USB Type B (Tx)

2×USB Type A (Rx)

LC

Power Supply

5V DC

Features

18Gbps data speed

HDMI 2.0 & HDCP 2.2 standards

4K@60Hz 4:4:4 UHD output

Real-time signal monitoring

OM4 300m transmission

Plug-and-play

EDID Transparent Transmission

HDMI+USB K/M Sync Extend

Environmental

0~55 Operating Temp



WXA-4KH-1D1U1E1A1R

Interface

HDMI, Audio(3.5mm)

SFP, IR

USB

RJ45(10/100M, TCP/IP)

Power Supply

12V DC

Features

4K@60Hz 4:4:4 UHD,

HDMI 2.0b/HDCP 2.2/DVI 1.0 compliant

HDMI video loop-out

DIP switch for audio separation & EDID

SFP (LC/SC) support 80KM Max.

KVM Function

10/100M TCP/IP

Bidi IR, RS232 default RS485 optional

Environmental

-25~55 Operating Temp



WXA-1080P-KVM

Interface

HDMI, Audio(3.5mm),

SFP, USB

Power Supply

12V DC

Features

1080P@60Hz HDMI+KVM+Audio+RS232

GPIO

20km SMF

HDMI loop-out

Plug-and-play

ESD protection

Environmental

-5~70 Operating Temp

HDMI over Fiber Converter



WXA-M4KH

Interface(Female)

HDMI
SFP

Power Supply

5V DC

Features

HDMI 1.4a/HDCP1.2
4K@30Hz (uncompressed)
10.3Gbps, 80km fiber transmission
USB-C power, hot-pluggable
EMI/RFI resistant

Environmental

-10~60 Operating Temp



WXA-M4KHRA

Interface

HDMI,
Audio(3.5mm)
SFP

Power Supply

5V DC

Features

HDMI 1.4a/HDCP1.2, hot-pluggable
4K@30Hz uncompressed (zero delay/loss)
10.3Gbps, 80km fiber transmission
DDC/CEC/HPD + stereo audio
850nm VCSEL/PIN detector
EMI/RFI resistant

Environmental

-10~60 Operating Temp



WXA-M4KHA

Interface

HDMI,
Audio(3.5mm)
SFP

Power Supply

5V DC

Features

HDMI 1.4a/HDCP1.2
4K@60Hz 4:2:0 (uncompressed)
10.2Gbps, 80km fiber transmission
DDC/CEC/HPD + stereo audio+RS232
Hot-pluggable
EMI/RFI resistant

Environmental

-10~50 Operating Temp

SDI over Fiber Converter



WXA-MHD Series

Interface(Female)

HDMI
SFP

Power Supply

5V DC

Features

HD-SDI compatible
8CH embedded audio
Auto eq & reclocking (270M – 1.48Gbps)
80km transmission Max.
Broadcast-grade uncompressed
Hot swap & plug
WDM/CWDM/DWDM support

Environmental

-20~70 Operating Temp

3G-SDI Optional



WXA-MHD-SR Series

Interface

HDMI,
Audio(3.5mm)
SFP

Power Supply

5V DC

Features

HD-SDI compatible
8CH embedded audio
Auto eq & reclocking (270M – 1.48Gbps)
80km transmission Max.
Broadcast-grade uncompressed
Hot swap & plug
Pathological pattern support
LED status indication

Environmental

-20~70 Operating Temp



WXA-MHD-BiS Series

Interface

HDMI,
Audio(3.5mm)
SFP

Power Supply

5V DC

Features

HD-SDI compatible
1CH Bi-directional HD-SDI
8CH embedded audio
Auto eq & reclocking (270M – 1.48Gbps)
80km transmission Max.
Broadcast-grade uncompressed
Hot swap & plug
Pathological pattern support
LED status indication

Environmental

-20~70 Operating Temp

SDI over Fiber Converter



WXA-HD-4S Series

Interface(Female)

HDMI
SFP

Power Supply

5V DC

Features

HD-SDI compatible
8CH embedded audio
Auto eq & reclocking (270M – 1.48Gbps)
80km transmission Max.
Broadcast-grade uncompressed
Hot swap & plug
WDM/CWDM/DWDM support

Environmental

-20~70 Operating Temp

3G-SDI Optional



WXA-HD-8S Series

Interface

HDMI,
Audio(3.5mm)
SFP

Power Supply

100-220V AC

Features

HD-SDI compatible
8CH embedded audio
Auto eq & reclocking (270M – 1.48Gbps)
80km transmission Max.
Broadcast-grade uncompressed
Hot swap & plug
Pathological pattern support
LED status indication

Environmental

-20~70 Operating Temp



WXA-HD-Bi4S Series

Interface

HDMI,
Audio(3.5mm)
SFP

Power Supply

100-220V AC

Features

HD-SDI compatible
1CH Bi-directional HD-SDI
8CH embedded audio
Auto eq & reclocking (270M – 1.48Gbps)
80km transmission Max.
Broadcast-grade uncompressed
Hot swap & plug
Pathological pattern support
LED status indication

Environmental

-20~70 Operating Temp